




923A - 823B

The uses of this bit are infinite: not only can you rout grooves and rabbets, but you can even T or dovetail joints on wood panels. Each bit features three carbide-tipped cutters, orange coloured PTFE coating and anti-kickback design. The 22mm bearing is included for a cutting depth of 12,8mm. The bit and the slot cutter are also available separately.




I mm	P mm	D mm	H mm	L mm		ORDER NO. S=Ø8mm	ORDER NO. S=Ø12,7mm
3	1,27	47,6	12,8	58	10	923.330.11A	
3,2	1,27	47,6	12,8	57,5	10		823.332.11B
4	2,07	47,6	12,8	58,3	10	923.340.11A	823.340.11B
5	2,86	47,6	12,8	63	10	923.350.11A	
6,4	4,45	47,6	12,8	60,7	10		823.364.11B

823



These three wing carbide tipped slot cutters feature anti-kickback three wing blade design and CMT's trademark orange PTFE Industrial Coating. All cutters feature an 8mm bore that fits CMT's arbors (items 7/8/924).

I mm	P mm	D mm	B mm		ORDER NO.
3	1,27	47,6	8	10	823.330.11
3,2	1,27	47,6	8	10	823.332.11
4	2,07	47,6	8	10	823.340.11
5	2,86	47,6	8	10	823.350.11
6,4	4,45	47,6	8	10	823.364.11



7/8/924



Assembly Illustration



DESCRIPTION		ORDER NO. S=Ø6mm	ORDER NO. S=Ø6,35mm	ORDER NO. S=Ø8mm	ORDER NO. S=Ø12,7mm
1 Slot cutter arbor without bearing without stop collar	10	724.061.00	824.061.00	924.081.00	824.121.00
1 Slot cutter arbor with bearing and stop collar	10	724.061.10	824.061.10	924.081.10	824.121.10
2 Slot cutter arbor without bearing	10			924.082.00	824.122.00
2 Slot cutter arbor with bearing	10			924.082.10	824.122.10

Spare parts

791.012.00	Ø8-22mm bearing
541.001.00	Stop collar for Ø6,35mm shanks
541.002.00	Stop collar for Ø12,7mm shanks
791.013.00	Ø12,7-22mm bearing
541.003.00	Stop collar for Ø6mm shanks
541.004.00	Stop collar for Ø8mm shanks

541.515.00	0,1mm spacer
541.516.00	0,3mm spacer
541.517.00	0,5mm spacer
541.518.00	1mm spacer
990.055.00	M5x12mm TSPEI screw
991.067.00	3mm hex key